

A M E N D E D

POLICY NO. 27B

BOARD OF COUNTY ROAD COMMISSIONERS  
OF THE  
COUNTY OF ST. CLAIR

SUBJECT: Minimum Width of Surfacing and Graded Shoulder for Other Than  
Subdivision Streets


AMENDED: April 17, 1990


Legal Citation:  
M.C.L. 221.20 (Act 283 of 1909 as amended)

It shall be the policy of the Commission that the minimum width of surfacing and graded shoulder be determined as follows for projects defined as HEAVY MAINTENANCE by Act 51, P.A. 1951:

| Design Speed & MPH | Width in Feet for Design Volume of: |                      |                       |                       |
|--------------------|-------------------------------------|----------------------|-----------------------|-----------------------|
|                    | Current ADT Under 400               | Current ADT 400-1000 | Current ADT 1000-4000 | Current ADT over 4000 |
|                    | Width of Surfacing                  |                      |                       |                       |
| 20                 | 20                                  | 20                   | 20                    | 22                    |
| 30                 | 20                                  | 20                   | 20                    | 22                    |
| 40                 | 20                                  | 22                   | 22                    | 22                    |
| 50                 | 20                                  | 22                   | 22                    | 22                    |
| 60                 | 22                                  | 22                   | 22                    | 22                    |
| 70                 | 22                                  | 22                   | 22                    | 22                    |
|                    | Width of Graded Shoulder            |                      |                       |                       |
| All                | 4                                   | 4                    | 5                     | 6                     |

Any interim or partial construction shall not diminish an existing geometric dimension of width for surfacing or shoulder and shall not steepen any existing frontslope. Interim or partial construction shall be defined as bridge or structure replacement, ditch cleaning, resurfacing or shoulder improvements.

  
\_\_\_\_\_  
Walter Street, Chairman

  
\_\_\_\_\_  
John D. Perry, Managing Director

Originally adopted: March 4, 1980  
Amended: February 11, 1986